SAPPHIRE

SAPPHIRE GPRO X080 10GB GDDR6

Product Specification

GPU: NAVI 22 Family Stream Processors: 2304

Compute Units: 36 Engine Clock: 2132 MHz Memory Clock: 16 Gbps

On board Frame Buffer: 10GB/160bit GDDR6

Bus Interface: PCI Expresss 4.0 x16

Display Output: N/A

External Power Connector: PCI Express 8 pin x 1

Cooling Solution: Active Dual Fan

Form Factor: 2 slot

Board Dimension: Dimension: 242(L)X 119.85(W)X 41(H)mm

Bracket: Full Height

Operating System: Linux Based System Only.

Packaging Options: Bulk




SKU: 32312-03-10G

Reference Ethash Performance

Default ~38.05 MH/s@~165W TGP, depending on the tuning of each card, ~41.6 MH/s@~93W could be reached. **

** Refer to Sapphire GPRO X080 Linux Ubuntu 20.04.3 installation & tuning guide for reference.



SYSTEM REQUIREMENTS

- PCI Express® based PC is required with one X16 lane graphics slot available on the motherboard.
- 500W (or greater) power supply with minimum one PCIE 8 pin power connector is required.
- Minimum 8GB of system memory. Recommended 16GB or more.
- Installation software requires a keyboard, a mouse, and a display.
- A display with digital input (HDMI[™] or DisplayPort) is required.
- Support Linux based system only
- 64-bit operating system required.
- Requires motherboard/CPU with integrated graphics processor and at least one display output.